

# Washer extractor

## W5600X

### Features and benefits

- **Compass Pro<sup>®</sup> microprocessor offers:**
  - Large display and one control knob for easy program selection
  - Language selection
  - Quick selection and option buttons for the most frequently used wash programs and options
  - Wash program packages optimized on Economy, Performance and Time. (Available on general programs)
- Extremely low water and energy consumption – see table below
- High extraction force for efficient dewatering
- Door with gasket and strong hinges built for heavy duty operation
- Stainless and galvanized steel in all vital parts for high degree of rust protection
- SuperBalance guarantees the correct extraction force



Images shown are a representation of the product only and variations may occur.

### Main options

- Stainless steel side panels
- Coin-meter
- Five compartment supply injector
- Third water inlet valve

Main specifications			W5600X	
Max. capacity filling factor 1:10	kg/lb		60/135	
Drum, volume	litre		600	
	ø mm		980	
Extraction	rpm		630	
G-factor			220	
Heating alternatives, 230/400V	electricity	kW	38/54	
	steam		x	
	non-heated		x	
<b>Consumption data "Normal 60°C"</b>			Full load, 60 kg	Half load, 30 kg**
<b>Economy*</b>				
Total time	min		51	49
Water consumption (cold+hot)	litre		380+100	360+80
Energy consumption (motor/heating/hot water)	kWh		0.75/2.85/6.4	0.7/2.3/5.1
Steam consumption	kg		13.9	11.1
Residual moisture	%		60	66

\* Water temperature 15°C cold water and 65°C hot water.  
 \*\* Depending on steam pressure.

Electrical connections					
Heating alternative	Main voltage		Heating power kW	Total power kW	Recommended fuse A
	Hz	Hz			
Electric heated	220-230V 3 ~	50/60	35-38	36-40	100
	240V 3 ~	50/60	38	40	100
	380-400V 3 ~	50/60	35-38	37-40	63
	415V 3 ~	50/60	38	40	63
	380-415V 3 ~	50/60	51.7-54.0	53.7-56.0	100
Non heated or steam heated	220-415V 1/3 ~	60	-	2.6	10

Water and steam connection		W5600X	
Water valves	DN	25	
Water pressure	kPa	200-600	
Capacity at 300 kPa	l/min	110	
Drain valve	∅ mm	75	
Draining capacity	l/min	170	
Steam valve	DN	20	
Steam pressure	kPa	300-600	
Floor requirements			
Frequency of the dynamic force	Hz	10.5	
Floor load at max extraction	kN	10 ± 15.6	
Sound levels			
Sound power/pressure level at extraction*	dB(A)	83/66	
Sound power/pressure level at wash*	dB(A)	69/52	
Heat emission			
% of installed power, max		5	
Shipping data**			
Weight	net, kg	775	
Shipping volume	m <sup>3</sup>	3.2	
Dimensions in mm			
A	Width	1173	
B(a)	Depth	1951	
B(b)	Depth	1193	
C	Height	1673	
D		33	
E		93	
F		600	
G		540	
H		1370	
I		125	
J		255	
K		227	
L		87	
M		85	
N		802	
O		103	
P		1544	
Q		1361	
R		587	
1	Operating panel	6	Drain
2	Door opening ∅ 535 mm	7	Liquid detergent supply
3	Detergent box	8	Electrical connection
4	Cold water	9	Steam connection
5	Hot water	10	Detergent supply injector, powder, right or left side (option)

\* Sound power levels measured according to ISO 60704.

\*\* Average data. Crated weight/shipping volume depends on configuration. Please contact logistics for exact measures.

